

Dot 600 Lite Modular



Foster+Partners, 2019



Indirect lighting suspension lamp. Lighting body in aluminium housing the integrated customized LED and the light optic system for diffused light. Reflector in PMMA. 1-10V or DALI dimming compatible. The decentralization kit is included. The lamp must be mounted with the dedicated ceiling rose.

FINISHINGS

Semi-Glossy Black

3000K - cod. 133M101SL00

2700K - cod. 133M101SLK27

Ultramatt White

3000K - cod. 133M102UM00

2700K - cod. 133M102UMK27

ALL RAL COATING AND GALVANIC FINISHES AVAILABLE UPON REQUEST

LIGHT EMISSION

Light source power: 9,8W

Power absorption: 9,8W

Light Emission: Diffuse

Light Direction: Indirect Downlight

Light Source: Custom Led Board

Source Flux 3000K: 1365lm@500mA

Emitted Flux 3000K: 490lm

Efficacy 3000K: 56lm/W

Source Flux 2700K: 1318lm@500mA

Emitted Flux 2700K: 463lm

Efficacy 2700K: 53lm/W

CCT: 2700/3000K

CRI: 90

Lifetime: >55000h

ELECTRICAL FACTS

Stand-by absorption: N/A

Mains Voltage: ----

Master output: ----

Ta max: 40°C

PACKAGING DATA

Box dimensions: cm

Volume: m³

Gross weight: kg

