

Foster+Partners, 2015



Table lamp for indirect and diffused lighting. The 18,8 W LED source is housed in the base. The light intensity is adjustable through a rotating dimmer base. Aluminium structure and transparent glass diffuser.

FINISHINGS

Anodised Black
3000K - cod. 14001X000
2700K - cod. 14001XOK27

Anodised Brass
3000K - cod. 14050X000
2700K - cod. 14050XOK27

ALL RAL COATING AND GALVANIC FINISHES AVAILABLE UPON REQUEST

LIGHT EMISSION

Light source power: 12,9W
Power absorption: 18,5W
Light Emission: Diffuse
Light Direction: Indirect Downlight
Light Source: Discrete LED
Source Flux 3000K: 1216lm@380mA
Emitted Flux 3000K: 315lm

Efficacy 3000K: 18lm/W
Source Flux 2700K: 1136lm@380mA
Emitted Flux 2700K: 305lm
Efficacy 2700K: 17lm/W
CCT: 2700/3000K
CRI: 97
Lifetime: >55000h

ELECTRICAL FACTS

Stand-by absorption: <0.5
Mains Voltage: 100/240VAC
Master output: 24VDC; max 0.83A
Ta max: 40°C

PACKAGING DATA

Box dimensions: 27x27x47 cm
Volume: 0,04 m³
Gross weight: 7,2 kg

