


Riccardo Marcuzzo, 2023



Perdue consists of an ogival shaped lighting body inside which is placed a sensor that detects a magnetic field. This turns the light on when the lamp comes into contact with its accessories (for table, wall, suspension) or with any metal body. The light intensity can be adjusted with a simple tap on the diffuser.

FINISHINGS

- Matt Black
3000K - cod. PRDM01010P00
- Metallic Champagne
3000K - cod. PRDM0116MT00
- Matt White
3000K - cod. PRDM01020P00
- Metallic Siler
3000K - cod. PRDM0155MT00
- Metallic Bronze
3000K - cod. PRDM0129MT00

ALL RAL COATING AND GALVANIC FINISHES AVAILABLE UPON REQUEST

LIGHT EMISSION

Light source power: 1,72W	Efficacy : 89lm/W
Power absorption: 4,2W	CCT: 3000K (2800K effective)
Light Emission: Diffuse	CRI: 90
Light Direction: Directional	Lifetime: >55000h
Light Source: Discrete LED	
Source Flux : 346lm@167mA	
Emitted Flux : 157lm	

ELECTRICAL FACTS

Stand-by absorption: <0.5
Mains Voltage: 100/264VAC
Master output: 5VDC; max 2A
Ta max: 40°C

PACKAGING DATA

Box dimensions: 25x10x10 cm
Volume: 0,002 m³
Gross weight: 0,4 kg

